



KOTEC CORP

21-15 3-CHO CHAYAMADAI SAKAI-SHI OSAKA 590-0115 JP

Material Designation: **KFR-30#**

Product Description: Polycarbonate (PC), furnished as pellets.

Color	Min. Thick. (mm)	Flame Class	HWI	HAI	RTI Elec	RTI Imp	RTI Str	IEC GWIT	IEC GWFI
ALL	1.6	V-0	-	-	80	80	80	-	-
CTI: -	IEC CTI (V): -	HVTR: -			D495: -			IEC Ball Pressure (°C): -	
Dielectric Strength (kV/mm): -		Volume Resistivity (10^xohm-cm): -						Dimensional Stability(%): -	
ISO Tensile Strength (MPa): -		ISO Flexural Strength (MPa): -						ISO Heat Deflection (°C): -	
ISO Tensile Impact (kJ/m²): -		ISO Izod Impact (kJ/m²): -						ISO Charpy Impact (kJ/m²): -	

Suffix optional excluding the letters "FR" and "FRT"

Report Date: 2/10/2000

Underwriters Laboratories Inc®

UL94 small-scale test data does not pertain to building materials, furnishings and related contents. UL 94 small-scale test data is intended solely for determining the flammability of plastic materials used in components and parts of end-product devices and appliances, where the acceptability of the combination is determined by ULI.